

## RENFROE MODELS LA AND LPA

LA vertical + 180 degree turn / LPA vertical + 180 degree turn + side pull



- Light weight ergonomic design
- Push button auxiliary lock allows 180 degree turn
- Lock open / lock closed feature facilitates attaching to and removal from plate
- LPA has pivoting lifting eye - permits side loading

Vertical Capacity (Tons)	Part Number	Plate Thickness A	Lifting Eye B	Max Height C	Max Width D	Weight	Clamp Orientation
1/2	LA	0 - 5/8	1 1/8	8 11/16	4 1/4	5	Vertical + 180° turn
1	LA	0 - 3/4	1 1/8	8 11/16	4 3/8	6	Vertical + 180° turn
2	LA	0 - 1	2 3/8	12 1/2	7 1/16	17	Vertical + 180° turn
3	LA	0 - 1	3 3/8	17	8 1/2	32	Vertical + 180° turn
1/2	LPA	0 - 5/8	1 1/8	8 11/16	4 1/4	5	Vertical + 180° + side pull
1	LPA	0 - 3/4	1 1/8	8 11/16	4 3/8	6	Vertical + 180° + side pull
2	LPA	0 - 1	1 7/8	12 1/2	7 1/16	17	Vertical + 180° + side pull
3	LPA	0 - 1	3 5/8	17	8 1/2	32	Vertical + 180° + side pull

## RENFROE MODELS J AND JP

J vertical + 90 degree turn / JP vertical + 90 degree turn + side pull



- Lock mechanism
- Lock open / lock closed feature facilitates attaching to and removal from plate
- JP has pivoting lifting eye - permits side loading
- Turn plate through 90 degree arc

Vertical Capacity (Tons)	Part Number	Plate Thickness A	Lifting Eye B	Max Height C	Max Width D	Weight	Clamp Orientation
1/2	J	0 - 5/8	2 3/8	12	5 5/8	10	Vertical + 90° turn
1	J	0 - 3/4	2 5/8	13 3/4	7	15	Vertical + 90° turn
2	J	0 - 1	3 1/2	17 3/8	8 3/4	36	Vertical + 90° turn
4	J	3/16 - 1 1/4	3 1/2	20 1/8	9 1/4	42	Vertical + 90° turn
1/2	JP	0 - 5/8	2 3/8	12	5 5/8	12	Vertical + 90° + side pull
1	JP	0 - 3/4	2 5/8	13 3/4	7	20	Vertical + 90° + side pull
2	JP	0 - 1	3 1/2	17 3/8	8 3/4	40	Vertical + 90° + side pull
4	JP	3/16 - 1 1/4	3 1/2	20 1/8	9 1/4	50	Vertical + 90° + side pull

## RENFROE MODEL FR

Vertical Only

- Most popular clamp
- Small and easy to handle
- Serrated gripping cams
- Lock closed feature
- Vertical only




Vertical Capacity (Tons)	Part Number	Plate Thickness A	Lifting Eye B	Max Height C	Max Width D	Weight	Clamp Orientation
1/2	FR	0 - 3/4	2 3/8	11 1/4	4 5/8	8	Vertical only
1	FR	0 - 3/4	2 5/8	13 3/4	5 7/8	14	Vertical only
2	FR	0 - 1	3 5/8	16 3/8	6 3/4	23	Vertical only
3	FR	0 - 1 1/4	3 5/8	18 3/8	7 5/8	30	Vertical only

## RENFROE MODEL HR

Horizontal



- Use in pairs, or tripod arrangement
- Serrated gripping cams
- Available with smooth non-marring cams




Vertical Capacity Ea.(Tons)	Part Number	Plate Thickness A	Lifting Eye B	Body Height C	Max Width D	Weight	Clamp Orientation
1/4	HR	0 - 2	1	2 3/4	3	3.5	Horizontal (use in pairs)
1/2	HR	0 - 2	1 3/8	4 1/4	7	14	Horizontal (use in pairs)
3/4	HR	0 - 2	1 3/8	4 3/8	7	19	Horizontal (use in pairs)
1 1/2	HR	0 - 2	1 3/8	4 3/8	7	23	Horizontal (use in pairs)
3	HR	0 - 2	1 3/8	6 1/4	7	24	Horizontal (use in pairs)
4	HR	0 - 4	1 3/8	7 3/4	7	44	Horizontal (use in pairs)

## RENFROE MODEL SCPA

Vertical + 180 Degree turn + side pull



- Can be used in rolling and forming
- Spring loaded cam
- Can be used for horizontal lifts (use in pairs or sets of pairs)




Vertical Capacity (Tons)	Part Number	Plate Thickness A	Lifting Eye B	Max Height C	Max Width D	Weight	Clamp Orientation
1/2	SCPA	0 - 3/4	1 3/4	12 3/16	6 5/8	8	Vertical + 180° + side pull
1 1/2	SCPA	0 - 1 1/4	2	14 3/16	8 7/16	15	Vertical + 180° + side pull
3	SCPA	0 - 2	3 x 6	21 3/8	10 3/16	24	Vertical + 180° + side pull
6	SCPA	0 - 2 1/2	3 1/2 x 7	27 3/4	14 3/8	57	Vertical + 180° + side pull

## RENFROE MODEL 300-S DRUM LIFTER

Vertical only



- Secure locking device
- Easy handling of one drum
- Vertical lift and transport



Vertical Capacity (Tons)	Part Number	Drum Diameter	Lifting Eye B	Max Height C	Max Width D	Weight	Clamp Orientation
3000	300-S	22 1/2	3 x 6	25	22 1/2	25	Vertical only