

DRUM HANDLING SLINGS

Lift-All drum handling slings provide an easy, inexpensive way to handle steel drums. Available in two styles to suit your needs for handling drums in the vertical or horizontal position.

Vertical Drum Handling Slings			
Part Number	Web Width (in.)	Drum Diameter (in.)	Sling Capacity (lbs.)
STANDARD HEAVY DUTY			
DSV602DX24	2	24	850
DSV602DX30	2	30	850
DSV602DX36	2	36	850
LIGHT DUTY			
DSV601DX24	1	24	300

Standard 55-gallon drum is 24" diameter. Other sizes available.

- Easily lift standing drums for transport.
- Tilt suspended drums to pour from open top or spigot.
- For use with ribbed steel drums, the ratcheting belly band tightens securely below the first rib.
- A wear pad is sewn on the inside of the lifting strap to prevent damage.
- Ratchet tightens and locks securely.
- The free end of ratchet strap is sewn to stay properly threaded.
- Vertical legs are sewn to an adjustable belly band to maintain proper position.



Part Number DSH601D

Horizontal Drum Handling Slings

Ideal for the quick and easy lifting of steel drums in the horizontal position.

Part number **DSH601D** uses 1" polyester sling webbing and is rated for 1,500 lbs.

- Strong 1" polyester webbing pulls drum hooks securely into rims at both ends of the drum during the lift.
- One sling fits multiple size drums.
- Easy to hook-up and disconnect.
- Uses a 1/2" diameter oblong link at the top for easy connection to hook.

Note: If used in a chemical environment, contact *Lift-All* for sling material options.