

HOW TO ORDER WEB SLINGS

- General Information
- Web Slings
- Round Slings
- Sling Protection
- Wire Rope
- Chain Slings
- Rigging Hardware
- Mesh Slings
- Load Huggers
- Tow Products
- Lift-All Hoists
- Hoist Rings
- Plate Clamps
- Lifting Devices

EE 1 8 02 T F X 12

Sling Type

- UU** - Type U - *Unilink™* Each End
- TC** - Type 1 - Triangle/Choker
- TT** - Type 2 - Triangle/Triangle
- EE** - Type 3 & 4 - Eye/Eye
- EN** - Endless
- RE** - Reverse Eye
- WL** - Wide Lift

Number of Plies
1, 2, 3 or 4

Web Class

- 1** - *Dura-Web™* 1000
- 2** - *Dura-Web™* 2000
- 8** - *Webmaster®* 1600 or *Tuff-Edge®* III
- 6** - *Webmaster®* 1200
- SH** - Stone Handling

Always protect synthetic slings from being cut or damaged by corners, edges and protrusions by using protection sufficient for each application.



Refer to Sling Protection section in this catalog.

Sling Length
Use actual pull to pull length (reach) in feet.

'X'

EYE TREATMENTS

Flat Eyes (Type 3)

- F** - Standard
- G** - Lined Bearing Point
- H** - Fully Lined
- I** - Wrapped Bearing Point
- J** - Fully Wrapped

Twisted Eyes (Type 4)

- T** - Standard
- U** - Lined Bearing Point
- V** - Fully Lined
- W** - Wrapped Bearing Point
- X** - Fully Wrapped

Exceptions: Class 1, 2 and SH slings

TAPERED EYE STANDARDS

Non-Tapered: 1" and 2" wide slings.
Tapered: 3" wider and up, in Class 6 & 8 slings only.

Note: Other treatments can be accommodated. Please specify at time of order.

Web Material

- T** - *Tuff-Edge* III
- D** - Polyester
- N** - Nylon

Sling Width in inches