

POLYESTER STAGE SLINGS

These lightweight roundslings are ideal for easy and inconspicuous suspension of stage sound and lighting equipment. Black sleeve material helps sling blend into the surroundings. *Lift-All* stage slings include all of the *Tuflex*® features and benefits except that the color coding of the slings is achieved by using a color-coded identification tag. Double-wall sleeve material is standard.



Part Number	Color of Tags	Rated Capacity (lbs.)*			Minimum Length (ft.)	Approximate Measurements			
		Vertical	Choker	Basket		Weight (lbs. / ft.)	Body Diameter Relaxed (in.)	Body Width @ Load (in.)	Minimum Hardware Diameter (in.)
BSEN30	Purple	2,600	2,100	5,200	1-1/2	.2	5/8	1-1/8	7/16
BSEN60	Green	5,300	4,200	10,600	1-1/2	.3	7/8	1-1/2	5/8
BSEN90	Yellow	8,400	6,700	16,800	3	.4	1-1/8	1-7/8	3/4



TUFLEX WIDE-LIFT

Wide Load Support and Balance

Tuflex wide-lift slings distribute the load over a wide area and offer better balance of larger loads, whether heavy or light.

Features and Benefits

Maintains all the basic *Tuflex* features plus...

Promotes Safety

- Wide body distributes load over wide area and offers improved stability.

Saves Money

- Bearing point of eyes can be shifted to prolong sling life.
- Custom sizes available to fit your needs.

Saves Time

- Standard eye length is 12", making hook-up easy and fast.
- Standard body width is 12", making load balancing easier.

Note:

Wide-lift slings should only be used in basket hitch.

Consult *Lift-All* for special requirements.



Code	Color of Eyes	Vertical Basket Hitch Rated Capacity* (lbs.)
WLEN30	Purple	5,200
WLEN60	Green	10,600
WLEN90	Yellow	16,800
WLEN120	Tan	21,200

* **WARNING**

Always protect Roundslings from corners, edges, or protrusions. Refer to the Sling Protection section of this catalog to choose the right protection product for your lift.